



Hårdmetall

Brotschar

Katalog 2011



magafor

Typ	Z	Obelagd	Cyl. skaft	Hörnfas 45°	Spiral 10°	Stål	Rostfritt	Gjutjärn	Alu	Titan
N	4-8	●				< 45 HRC	●	●	●	●

Universal hårdmetallbrottsch
På varje 0,01 mm



Ø d1 Diam.	Ø d2 Skaft h8	l1 Total längd	l2 Spiral längd	ap	z	8600 Obelagd
0,60 - 0,69	= d1	33	7	10	4	
0,70 - 0,79	= d1	33	7	10	4	
0,80 - 1,05	= d1	33	7	10	4	
1,06 - 1,55	= d1	40	10	24	4	
1,56 - 2,36	= d1	50	11	31	4	
2,37 - 3,75	= d1	57	15	38	6	
3,76 - 4,25	4	75	19	49	6	
4,26 - 4,75	4,5	80	21	51	6	
4,76 - 5,30	5	86	23	59	6	
5,31 - 5,80	5,5	93	26	65	6	
5,81 - 6,70	6	101	28	71	6	
6,71 - 7,55	7	109	31	78	6	
7,56 - 8,55	8	117	33	84	6	
8,56 - 9,55	9	125	36	88	6	
9,56 - 10,05	10	133	38	97	6	
10,06 - 11,05	10	133	38	97	6	
11,06 - 12,05	12	151	44	110	6	
12,06 - 13,05	12	151	44	110	6	
13,97 - 14,05	14	160	47	110	8	
14,97 - 15,05	14	162	50	112	8	
15,97 - 16,05	16	170	52	117	8	
17,97 - 18,05	16	182	56	129	8	
19,97 - 20,05	16	195	60	142	8	

Ø d1 Diam.	Tolerans	l2 Spirall längd	l2 Spiral längd
0,60 - 3,00	0 + 0,003	± 1	+ 1
3,01 - 6,00	0 + 0,004	± 1	+ 1
6,01 - 20,20	0 + 0,005	± 1	+ 1

Z	Obelagd	Cyl. skaft	Hörnfas 45°	Spiral 10°	Stål	Rostfritt	Gjutjärn	Alu	Titan
4-8					< 45 HRC	●	●	●	●


Universal hårdmetallbrottsch H7


Ø d1 Diam.	Ø d2 Skaft h8	l1 Total längd	l2 Spiral längd	z	MS 402 Obelagd
1,0	2	40	5	4	
1,5	2	40	8	4	
2,0	2	49	11	4	
2,5	3	57	14	4	
3,0	3	61	15	4	
3,5	4	70	18	4	
4,0	4	75	19	4	
4,5	5	80	21	4	
5,0	5	86	23	6	
5,5	6	93	26	6	
6,0	6	93	26	6	
6,5	7	101	28	6	
7,0	7	109	31	6	
7,5	8	109	31	6	
8,0	8	117	33	6	
8,5	9	117	33	6	
9,0	9	125	36	6	
9,5	10	125	36	6	
10,0	10	133	38	6	
10,5	11	133	38	6	
11,0	11	142	41	6	
11,5	12	142	41	6	
12,0	12	151	44	6	
12,5	13	151	44	6	
13,0	13	151	44	6	
13,5	14	160	47	8	
14,0	14	160	47	8	
14,5	15	162	50	8	
15,0	15	162	50	8	
15,5	16	170	52	8	
16,0	16	170	52	8	
18,0	18	182	56	8	

Typ	Z	TiAIN	Cyl. skaft	Hörnfas 45°	Spiral 10°	Stål	Rostfritt	Gjutjärn	Alu	Titan
N	2	●				< 45 HRC	●	●	●	●

Universal hårdmetallbrottsch H7


Ø d1 Diam.	Ø d2 Skaft h8	l1 Total längd	l2 Spiral längd	ap	z	8680 Obelagd
3,0	3	90	14	70	6	
3,5	3,5	90	14	70	6	
4,0	4	105	16	80	6	
4,5	4,5	105	16	80	6	
5,0	5	115	16	90	6	
5,5	5,5	115	16	90	6	
6,0	6	130	16	100	6	
7,0	7	140	18	110	6	
8,0	8	160	18	130	6	
9,0	9	175	18	140	6	
10,0	10	190	20	150	6	
11,0	10	190	20	150	6	
12,0	12	220	22	170	6	
13,0	12	220	22	170	8	
14,0	12	220	22	170	8	
15,0	12	220	22	170	8	
16,0	16	230	25	180	8	
18,0	16	230	25	180	8	
20,0	16	230	25	180	8	



**Beställ verktyg enkelt och smidigt
genom vår WEBSHOP**

www.wiklundsverktyg.se

